



priključci za traktor tuber  
tractor tuber attachments  
traktor tuber zubehörs

PV 3000

PV 4000



## Tehnički podaci

	PV-2000	PV- 3000	PV- 4000
Dimenzija sanduka:	1500x2500 mm	1800x3000 mm	1800x3000 mm
Kipanje:	3 strane	3 strane	3 strane
Visina poda od tla:	884 mm	894 mm	894 mm
Trag kotača:	1150 mm	1500 mm	1500 mm
Sistem kočenja:	hidraulički, zračni	hidraulički, zračni, naletni	hidraulički, zračni, naletni
Centralni sistem otvaranja:	stražnji i bočni	stražnji i bočni	stražnji i bočni
Dopuštena brzina vožnje:	25 km/h	25 km/h	25 km/h
Vlastita težina:	780 kg	900 kg	960 kg
Kotači:	10.0/80-12"	10.0/75-15,3"	10.0/75-15,3"
Nosivost:	2000 kg	3000 kg	4000 kg
Opcija dodatnih stranica:	400 mm	400 mm	500 mm

## Technical features

	PV-2000	PV-3000	PV-4000
Box dimensions:	1500x2500 mm	1800x3000 mm	1800x3000 mm
Tipping:	3 sides	3 sides	3 sides
Ground clearance:	884 mm	894 mm	894 mm
Track:	1150 mm	1500 mm	1500 mm
Brakes:	hydraulic, air inertia brake system	hydraulic, air inertia brake system	hydraulic, air inertia brake system
Central locking system:	rear and side	rear and side	rear and side
Max. speed:	25 km/h	25 km/h	25 km/h
Weight:	780 kg	900 kg	960 kg
Wheels:	10.0/80-12"	10.0/75-15,3"	10.0/75-15,3"
Carrying capacity:	2000 kg	3000 kg	4000 kg
Optional side wall:	400 mm	400 mm	500 mm

## Technische Merkmale

	PV-2000	PV-3000	PV-4000
Ladefläche:	1500x2500 mm	1800x3000 mm	1800x3000 mm
Kippen:	3 Seitenkipper	3 Seitenkipper	3 Seitenkipper
Ladehöhe:	884 mm	894 mm	894 mm
Spurweite:	1150 mm	1500 mm	1500 mm
Bremse:	Hydraulisch Luftbremssystem Auflaufbremse	Hydraulisch Luftbremssystem Auflaufbremse	Hydraulisch Luftbremssystem Auflaufbremse
Verriegelung:	Seitenwände und Heckklappe Klappbar	Seitenwände und Heckklappe Klappbar	Seitenwände und Heckklappe Klappbar
Ausführung:	25 km/h	25 km/h	25 km/h
Gewicht:	780 kg	900 kg	960 kg
Bereifung:	10.0/80-12"	10.0/75-15,3"	10.0/75-15,3"
Ladekapazität:	2000 kg	3000 kg	4000 kg
Optional aufsatzbordwände:	400 mm	400 mm	500 mm